

Martin® Non-Impacting Railcar Vibrator

This lightweight, low-noise system combines a non-impacting linear vibrator with a urethane mounting shoe. The [Martin® Non-Impacting Railcar Vibrator](#) provides up to 1000 lbs (454 kg) of force to unload the most stubborn materials.



BENEFITS

- Improves Efficiency**
 Linear vibrator provides powerful force to boost material flow.
- Low Noise**
 Non-impacting vibrator and urethane mounting shoe eliminate metal-to-metal noise.
- Easy to Handle**
 Lightweight vibrator and shoe make mounting/dismounting a "no-strain" procedure.
- Small But Mighty**
 Compact vibrator and mount assembly provides plenty of power to unload the most stubborn materials.
- Saves Your Ears**
 No hearing protection required; non-impacting vibrator on urethane foot produces only 80–85 db.
- Gives Your Back a Break**
 Vibrator and wedge system weighs only 33 lb (15 kg), reducing risk of injury from manhandling large, unwieldy vibrators into railcar brackets.
- Saves Your Energy**
 Air-efficient design operates on air supply from 40 to 80 psi (2.8 to 5.5 bar); consumes only 15 cfm at 80 psi (425 L/min at 5.5 bar).
- Guaranteed Performance**
 MP3 Vibrator is covered by Martin Engineering's *Absolutely, Positively, No Excuses* Guarantee.

NOTES

- All units require FRL Kit (Air Line Filter/Regulator/Lubricator) for proper operation.
- Suggested operating temperature 30°F (-1°C) and above.

ACCESSORIES

Description	Part Number
Female Wedge Bracket (LBF)	12735
Control Line Kit	39504
Air Motor Oil (qt)	14766

SPECIFICATIONS

Model	P/N	Piston	Air Pressure	CFM	VPM	Force	Noise Level	Weight
Martin® Non-Impacting Railcar Vibrator	36889	4"	40 psi	7	2100	350 lbs	80 db	33 lbs
			60 psi	11	2500	650 lbs	83 db	
			80 psi	15	2800	1000 lbs	85 db	



Martin Engineering Australia Pty Ltd.
 20 Ern Harley Dr - Burleigh Heads, QLD, 4220 - Australia
 1300 627 364
www.martin-eng.com.au

