

WWW.DRYCARGOMAG.COM

ISSUE NO. 257 MAY 2022



FEATURES



The world's leading and only monthly magazine for the dry bulk industry

Keeping fugitive material in its place



Dust accumulation on rolling components can cause abrasive damage and premature failure.

When tonnes of bulk material hit a moving conveyor belt, three things happen: fines scatter in random directions, cargo shifts and dust becomes airborne, writes Daniel Marshall, Product Engineer at Martin Engineering.

The impact creates turbulent air pressure inside the transfer chute that escapes from any available gap, carrying dust and fines with it. A properly designed enclosure will manage bulk solids, allow cargo to settle in the center of the belt and contain most of the dust inside a settling zone enclosure. Well-designed conveyor loading zones also keep walkways clear from spillage and control dust emissions, allowing hazard-free inspections and maintenance.

THE COST OF SPILLAGE

If left uncontained, fugitive material in the form of dust and fine particle spillage will increase labor costs for cleanup, foul equipment, potentially encapsulate the belt and pose a serious safety hazard. A dirty and dusty environment also discourages workers from doing regular maintenance on the problem area and negatively affects morale.

Since trips and falls are regularly among the most common workplace accidents, Occupational Safety and Health Administration (OSHA) inspectors are constantly on the lookout for those hazards. Dust levels are also strictly regulated by OSHA, and permit violations are often accompanied by fines and potential downtime.

SEALED CHUTE COMPOSITION

A well-designed loading zone typically

consists of a combination of components. These include:

- An enclosed transfer chute should be long enough to give dust and fines time to settle.
- A heavy-duty belt support system absorbs impact, protects the belt and can handle rapidly shifting heavy material.
- Closely spaced idlers help avoid sags in the belt that allow gaps where fines can escape and ease material disruption from bouncing.
- Externally adjustable or self-adjusting skirting contains fine particles and adapts to fluctuations in the belt plane.
- Easily serviced wear liners can be changed from outside the chute without confined space entry.
- Dust curtains set strategically throughout the enclosure control airflow and help settle dust.
- Dust bags or mounted air cleaners collect tiny, highly active particles.
- A sealed tail box protects the tail pulley from the backflow of fines, dust and spillage.
- Exit curtains prevent fugitive dust from escaping from the end of the chute.

CASE STUDY

A US power generating facility has drastically reduced dust and spillage from its biomass fuel handling system, helping to prevent fugitive material from reaching nearby homes and businesses. The fuel includes wood from open loop sources (such as waste wood, limbs and agricultural waste) and closed loop sources (dedicated



External wear liner and dual self-adjusting seal with belt support. © 2022 Martin Engineering Company

crops of trees), with a goal of averaging 75% of the power generated from biomass fuels.

The material handling system at the site is critical to the plant's efficiency, but from the time it began operations, controlling dust and spillage was a challenge. Because of the largely residential area in which the facility is located, controlling carryback and spillage were among the top priorities. After a thorough evaluation of the material handling system, Martin Engineering technicians began by installing primary and secondary belt cleaners on all four conveyors.

The primary units on each belt are brush-type cleaners, a unique electricpowered design that provides an effective, cost-efficient solution for residual beltborne material. The secondary units are versatile 'deflected blade' designs that feature a gentle pressure to prolong service life and prevent belt damage.

"We installed electric brush cleaners on each conveyor, because they're very effective on the type of cleated belts used at this facility," observed the Martin Engineering Territory Manager. "The rotating brush delivers good cleaning performance in difficult applications, including belts with ribs, grooves or chevrons, and belts carrying sticky materials or stringy fibres."

Part of the problem was that some of the conveyor sections were at steep angles, and with the variable size and moisture content of the fuel, there were always chips that would fall back down. To address the issue, Martin Engineering technicians removed troublesome sections of the conveyor and replaced them with specially-engineered transfer points. They also modified existing transfer points, installing drop chutes to help eliminate dust and transfer chutes with a hood-andspoon design to improve the material flow.

"Reducing the material turbulence during transfers is key to preventing

108

MAY 2022

fugitive dust," observed a Martin technician. "By managing the material speed and direction, transfer chutes help minimize impact and wear on liners and belts, while containing the dust and spillage that are often generated at transfer points," he said. "All of the chutes were field-fabricated, which helped us get an exact fit and minimize lead time."

The transfer chutes employ special geometries that capture and concentrate the material stream as it travels through. Each unit is customized to suit the specific material characteristics and conveyor systems of the individual customer. They provide the dual benefits of minimizing aeration and preventing buildup within the chute, particularly important when dealing with combustible materials.

The installation team also placed electric rotary vibrators in key locations on drop chutes to reduce the potential for plugging. To further ensure control of fugitive material, settling zones were created at the transfer points to slow the air speed, with dust curtains to contain airborne particles.

Finally, skirtboard sealing systems were installed on the sides of the loading zones to contain dust, eliminate spillage and reduce cleanup. The dual-sealing system incorporates a primary seal clamped on the steel skirtboard to keep lumps on the belt and a secondary or 'outrigger' strip to capture any fines or dust particles that pass beneath the primary seal. The secondary seal lies gently on the belt and self-adjusts to maintain consistent stripto-belt pressure, despite high-speed material movement and fluctuations in the belt's line of travel. The unique design incorporates two wear surfaces on a single elastomer sealing strip, installed along the bottom of the skirtboard. When the bottom side of the strip against the belt is worn, the sealing strip is simply flipped over to deliver a second service life.

With the modifications in place, the facility reports significant reductions in spillage and airborne dust. "We're very pleased with the results we've seen in fugitive material control," said a source close to the project. "We're now reviewing several other conveyor sections to determine the opportunities for additional dust control measures. Our goal has always been to provide customers with safe, reliable power that's delivered produced and in an environmentally-responsible manner, and this work is a reflection of that commitment."



A field-fabricated drop chute fitted with a vibrator to improve material flow to the new transfer point.



A new head chute and brush cleaner reduced dust by an estimated 95% at the bucket elevator.

