A Publication Dedicated to Mining and Aggregates Worldwide

MINIC

SEPTEMBER Vol. 41 No. 6

Bulk Material Handling

Joe Dos Santos President and founder of Dos Santos International



Published by Al Skinner, Inc.

Editor/Publisher Al Skinner E-mail: alskinner@ntelos.net

Managing Editor Christina Martin E-mail: cpm@ntelos.net

Staff Writer/Field Reporter Debra McCown Thomas

Circulation Changes E-mail to cpm@ntelos.net

Production Department E-mail Artwork or Inquiries to: cpm@ntelos.net

Advertising Sales Lisa Roper Phone (864) 278-8227 E-mail: lisa.roper@charter.net

Chuck Roper Phone (864) 546-8978 E-mail: chuck.roper@charter.net

> Website Administrator Chuck Jelderks

Corporate Office Phone (304) 342-4129 Toll Free (800) 235-5188 P.O. Box 6247, Charleston, WV 25362 629 Virginia St., W, Charleston, WV 25302

Web Portal www.miningpeople.org

Subscribe on-line when visiting Web site. Subscription rate \$25 annually within the United States. \$50 for Canadian and overseas subscriptions. Send payment to above address. Mining People Magazine is mailed direct to mining and aggregates executives with buying power in the United States, Canada, Mexico and overseas. Each copy is mailed specifically to company presidents, CEO's, vice presidents, engineers, purchasing agents, and mine supervisors. Additional copies are distributed at shows, conferences and meetings. Editorial material should be submitted to the editor at the address above by the 15th of the month prior to publication. All original material including advertising design, copy illustrations and

signatures conceived and developed by Al Skinner Inc for use by its publication are for express use of this publication. All rights reserved.© Advertising rates and editorial calendars are available upon request by calling Lisa Roper at (864) 278-8227.



amazed by

CleanScrape[®], it's been on for a year now and I haven't touched it. This material is sloppy, it's just muck that we're running. And then you look at the return side of the belt and the proof is right there. Absolutely phenomenal. Try it out for yourself, it's amazing.

– Trey Poulson | Fairplay Gold Mine, Colorado, USA



visit martin-eng.com | 800.544.2947 or 309.852.2384 ® Registered trademark of Martin Engineering Company in the US and other select locations. © 2018 Martin Engineering Company. Additional information can be obtained at www.martin-eng.com/ipademarks and www.martin-eng.com/ipademts.

Read about Martin Engineering's Innovative Stainless Steel Conveyor Belt Cleaner on page 26!

Mining People Magazine is available in print and on-line. Subscribe on-line to receive your electronic issue at no extra charge! Easy-to-read, flip-page format Or Send request to info@miningpeople.org.

The Most Unique Blend of Editorial and News in the Mining and Aggregates Industries. www.miningpeople.org




Next Issue: Oct/Nov Buyer's Guide Issue

September 2019 Vol. 40 No.6

Features

Dedicated to Mining and Aggregates Worldwide




Need to Move Dirt? Give it a Hug The Story of Dos Santos International by Debra McCown Thomas



Elk Return to Appalachia on Reclaimed Mine Sites Article and photos by Debra McCown Thomas

On the cover....

Joe Dos Santos, President and founder of Dos Santos International Background: Looking down from the top of a DSI Sandwich belt high angle conveyor in Aceralia, Spain. This conveyor elevates coal at a 75 degree angle, replacing a problematic pocket belt system.



Departments

Buyer-Friendly Ad Index "Find it Fast"	4
Editorial	
Mining People Comments	
Capsule News	
Worldwide News	
Mining People in the News	
Events	
Energy News	40
Product News	42
Advertising Index	
Professional Directory / Classified	

Articles of Interest

The New Elk Hard Coking Coal Mine by Allegiance Coal Limited	. 22
Ohio Department of Natural Resources' Abandoned Mine	
Land Program Wins National Award	. 24
Innovative Stainless Steel Conveyor Belt Cleaner: High	
Performance + Long Life=Reduced Ownership Cost	. 26
United States to "Drown the World" in Oil	. 41
Stronger and Greener: A Century Old Coalfield	
Gets a New Life in China	. 44



Buyer-Friendly Index

ABRASION / IMPACT RESISTANT MATERIALS
CBP Engineering Corp. (46)www.cbpengineering.com
HardSteel, Inc. (45, 46)www.hardsteel.com
Hardface Technologies by Postle Industries (46)
www.hardfacetechnologies.com
AUTOMATED SAMPLING SYSTEMS
Precision Samplers, Inc (47) www.precisionsamplers.com
BELT CLEANING SYSTEMS
Richwood (47) www.richwood.com
COAL PREPARATION
Farnham & Pfile Engineering & Construction (47)
www.farnham-pfile.com
CERAMIC PROCESS EQUIPMENT
Ceramic Technology (49)
CONTRACTORS
Cowin & Company Inc. (47) www.cowin-co.com

CONVEYOR ACCESSORIES
Richwood (47) www.richwood.com
CONVEYOR SCRAPERS
Martin Engineering (3)www.rmartin-eng.com
CONVEYORS
Jennmar Corp. (9) www.jennmarcorp.com
DISTRIBUTORS / ENGINEERED PRODUCTS
RM Wilson Co, Inc. (52 (BC)) www.rmwilson.com
United Central Industrial Supply Co., Inc. (2)
www.unitedcentral.net
EQUIPMENT REBUILD & REPAIR
Eastern Rebuild & Repair(46)
EVENTS
CONEXPO-CON/AGG (7) www.conexpoconagg.com
SME Annual Conference (25) www.smeannualconference.com

FANS / FAN REPAIR
Pauls Fans (37, 48) www.paulsfans.com
GEAR & GEAR BOX REPAIR
Hanson Gear Works (37, 48) www.hansongearworks.com
IMPACT SADDLES
Richwood (49) www.richwood.com
PIPING & PUMPING SYSTEMS / HOSE
Lee Supply Co., Inc. (48) www.leesupply.com
PIPING, VALVES & FITTINGS / HOSE
JABO Supply (50) www.jabosupply.com
RAISE BORING
Raisebor (48)www.raisebor.com
ROCK CONSOLIDATION & VOID FILL
Strata Worldwide (49) www.strataworldwide.com
TIRES
Setco Tire & Rim Assembly (5, 49) www.setcosolidtire.com

Innovative Stainless Steel Conveyor Belt Cleaner: High Performance + Long Life = Reduced Ownership Cost

The new secondary belt cleaner is engineered to minimize maintenance and conveyor stoppages.

A new secondary conveyor belt cleaner has been engineered specifically for challenging applications where traditional designs fail to deliver the necessary performance or wear life. The CleanScrape® Secondary Cleaner (CS2) from Martin Engineering is particularly effective in conditions where continuous production is a high priority or cleaner service is difficult, including corrosive or high-temperature environments. Typically requiring just one re-tensioning during its lifespan, the extremely low maintenance requirements and outstanding cleaning ability help reduce cost of ownership in a wide range of industries, such as mining, coal processing, quarrying, cement production, scrap and other bulk material handling operations.

An excellent solution for areas with restricted space, the unique all stainless steel design incorporates a matrix of specially-engineered carbide tips and is tensioned lightly to prevent damage to the belt or splices. Despite extremely low contact pressure between belt and cleaner, it has been shown to effectively remove potential carryback material that was not dislodged by a primary cleaner. The carbide cleaning surfaces deliver excellent performance, and the unit's light touch helps protect against belt wear.

The CS2 can be used with any primary cleaner, but was engineered to be paired with the company's original CleanScrape® Primary Cleaner (CS1). When used together, they form a rugged, low-maintenance system that effectively removes carryback, helping to prevent fugitive material and the associated cleanup. The system represents a revolutionary concept that delivers superior cleaning and up to 4x the service life of conventional designs, with half the maintenance. The combination has been, shown to remove as much as 99% of the carryback in most belt cleaning applications. The reduced service requirements and exceptional durability deliver a low life cycle cost, while allowing crews to focus on other tasks.

"Many carbide-tipped belt cleaners require high pressure against the belt in order to be effective, and they typically need to be re-tensioned often throughout their service life," explained Chief Technology Officer Paul Harrison. "Like the CS1, this design is extremely effective with light tension against the belt, which helps avoid the damage to belts and slices that can occur with other carbidetipped secondary cleaners. And because it only needs tensioning once during its lifespan, the maintenance requirements are very low."

Harrison said that the negative rake angle of the CS2 is also key to the new design. "Some manufacturers use a positive angle of attack at the secondary position, which is greater than 90 degrees," he continued. "That's common in a urethane primary cleaner, which is tensioned tightly against the pulley. But using a 'peeling' action in a secondary cleaner can damage and prematurely wear the belt cover. It can be catastrophic on "beaver tails" (small sections of belt damage where a section of the top cover has separated from the belt carcass). With a negative rake angle and the 'scraping' action it provides, the CleanScrape Secondary Cleaner delivers outstanding performance, while mitigating potential belt damage."





Intelligent Design

The "free flow" design, with an absolute minimum of exposed surface area, delivers optimum cleaning results while allowing material to pass through the arms and return to the cargo flow. The compact system requires very little free space, and can be easily installed inside or outside of discharge chutes, while the crowned main frame compensates for cupping or wear of the center of the belt.

The carbide blade tips have a small corner radius to protect against belt damage, and each one is supported on spring-loaded arms at both ends. The load springs allow independent blade rotation back and forth, as well as up and down. This range of motion provides equal load pressure across each blade, bypassing obstructions and conforming to ever-changing belt undulations. The unique design holds the blade in an effective cleaning position but allows the blades to retreat into a safe position for reversing belts or rollback.

"This new design is engineered to withstand high production demands in which maintenance and conveyor stoppages must be minimized," said Harrison. "The combination of CleanScrape primary and secondary cleaners offers these customers a matched set of components that require half the maintenance of conventional designs, helping to reduce service costs and production downtime."

The CleanScrape Secondary Cleaner is suitable for conveyor speeds up to 5 m/s (900 fpm) on belts with vulcanized splices, and up to 3 m/s (600 fpm) on belts with mechanical splices. Supplied with a stainless steel tensioner, it can withstand temperatures as high as 260°C (500°F). Available for any size belt in full belt widths or 150 mm (6 in) less than belt width, the unit can be specified with Martin's unique Safe-To-Service technology -- giving maintenance personnel the ability to work on the assembly safely from outside the chute wall or conveyor structure -- without breaking the safety plane.

"Some plants require a confined space permit if workers are going to reach through the outer edge of the chute work," Harrison added. "With all adjustments being made from the operator side, there is no need to enter a confined space."

Engineered to disengage from the tensioner, Safe-To-Service designs allow the cleaner to be pulled out far enough to take out a quick-release pin and remove the assembly. Once the new unit is installed, it's simply pushed back into position and the tensioner re-engaged. The one-pin procedure makes replacement an easy, no-tool operation performed from the outside of the chute.

Both of the CleanScrape Cleaner designs meet all regulatory requirements for use in underground mining. Pre-assembled primary and secondary belt cleaners for stan-


dard belt widths are supplied ready for installation. The primary cleaner can also be supplied in coiled lengths of 12.4 meters (40.68 feet), allowing users to cut to length as needed and not have to stock multiple belt width sizes.

"The CleanScrape Cleaner System represents an entirely new dimension in belt cleaning," Harrison concluded. "We're so confident in the performance of these products that we provide a money-back satisfaction guarantee."

For more information, contact info@martin-eng.com, visit www.martin-eng.com, or call (800) 544-2947. © 2019 Martin Engineering Company. All rights reserved.



The CS2 typically requires just one retensioning during its lifespan, helping to reduce cost of ownership.



A negative rake angle delivers outstanding cleaning performance with low belt pressure.



The unique stainless steel design incorporates a matrix of spring-loaded carbide tips.