

www.zkg.de

REDUCE YOUR CO_POOTPRINT with CC/CLAAY calcined clay and grinding

A collaboration of





www.c-clay.com

On any belt conveyor system that moves bulk materials, the belt must run straight and true to maximize its life, minimize fugitive material and safety hazards, and achieve high system efficiency. There can be many consequences of a mistracking belt, but all result in higher costs and increased maintenance. Even a slight belt misalignment can lead to a variety of issues, from small annoyances to full-blown catastrophes.

TEXT R. Todd Swinderman P.E., CEO Emeritus, Martin Engineering, Neponset/USA

MARTIN ENGINEERING

Identifying and addressing conveyor idler issues

The most obvious effects of mistracking belts include spillage and dust that require personnel to do cleanup, which is unproductive work that introduces risks from activities in close proximity to the moving conveyor. Spillage from noncentered cargo often gets into idlers and pulleys, reducing bearing life and causing them to seize, leading to friction damage on the belt and potentially starting a fire.

"Knocking" an idler with a mallet to change its position



A misaligned belt can also come in contact with the stringer, causing fraying, shredding or splice damage. Great lengths of valuable belting can be destroyed with surprising speed, and even the support structure itself can be damaged. A compromised bracket or support can cause a catastrophic idler failure, which could damage other components of the system and require extensive downtime to repair. Further, there is potential for injury from a damaged belt or loose idler not to mention the increased exposure to injury from too frequent a need to clean.

"I've been working around conveyors for 20 years, and I've seen thousands of belts," observed Martin Engineering Process Engineer Dan Marshall. "I've seen just about every problem that can be caused by a mistracking belt, but one thing I've never seen is a belt that runs true right out of the box. All conveyors, no matter how well designed and built, have some belt wander."

A wide variety of circumstances can lead to mistracking, and operators have tried many things to correct the alignment. Some have elected to place an obstacle such as a block of wood in the belt path, so it won't travel too far out of line. This occasionally improves the situation, but more often it's just temporary and the belt will eventually slice through the obstacle.

Many operators have realized that pivoting an idler is a quicker and more effective way to steer a belt. This common approach is called "knocking an idler," striking it with a hammer to move it slightly and realign the belt.

Equipment manufacturers have also designed components to help align a belt, and these solutions can be successful in specific applications. They include specially-shaped rollers, angled idlers and devices that apply pressure to the belt edge to push it back in line.



1 Different component designs for improving belt alignment



3 Multi-Pivot Trainer for the load-carrying run

"While these mechanisms can improve a belt that's consistently off-center in one direction, they do not react to dynamic belt movement, meaning that they don't correct intermittent belt wander," Marshall continued. "To combat such changing conditions, engineers designed the tracking idler. Unlike the edge correction approach, the device senses belt movement in either direction, and pivots the idler slightly to steer the belt back into position. It doesn't apply a great deal of force to the edges, which can damage a belt and splices. When the belt is running true, it remains centered, and when it senses a misaligned condition, it gently corrects the belt."

Unfortunately, to accommodate limited space availability, tracking idlers typically have short sensing arms. This requires a fairly large belt displacement to create a small movement of the idler. While these designs do tend to improve tracking, there are limits to how much correction they can deliver, and short sensing arms can actually pinch a belt if the idler pivots too far. To combat this, some operators choose to "tie off" a tracking idler to limit its movement. While the practice can help preserve the belt, it doesn't address significant mistracking.

To overcome the limitations of existing belt alignment devices, Martin Engineering has invented and patented a Multi-Pivot Belt Tracker, which employs sensors, pivoting idlers and geometry to align a wandering belt. The sensors avoid pinch-



2 Tracking idler



4 Multi-Pivot Trainer for the return run

ing the belt, and the engineered geometry amplifies any detected misalignment to create a greater pivot.

Multi-Pivot Belt Trainers use longer arms than other designs, positioning the guide rolls further from the pivot roller, as well as closer to the belt edge. The closer proximity allows guide rolls to sense very slight misalignments and make immediate corrections. Rather than waiting for a powerful mistracking force, the longer arms require considerably less pressure to move the pivot roller. The result is better correction with no pinch points and less wear on conveyor and tracking equipment, for longer and more efficient service life. Specific designs are available for both the load-carrying belt path and the return run.

"Installing trackers is the economical solution, but operators should do a full analysis and consider also addressing other causal issues," Marshall added. "By focusing solely on belt alignment, plant personnel may miss other opportunities to increase production and relieve some of the burdens on their system."

Keeping the belt centered and moving quickly is the key to high production, controlled operating cost and a safer workplace. "Misalignment causes downtime and costs money," Marshall concluded. "But nothing causes more downtime and expense than a destructive belt fire or other catastrophe as a result of inattention to mistracking problems." www.martin-eng.com



26-27 OCTOBER 2023, LYON/FRANCE

Lyon will be the venue for the second CarbonZero Global Conference and Exhibition



CarbonZero: Alternative Fuels and Raw Materials 2023 Conference and Exhibition

CarbonZero Global Conference and Exhibition – the second edition – is announced for October 26 and 27, 2023 in Lyon/France to again reunite the heads of companies who are willing to actually take a stand and act. The two-day event is bringing together C+ executives and decision-makers from cement manufacturing companies, construction and real estate players, environmental specialists, equipment and technology producers as well as Innovation, Research and Development, Academia, Authorities and Think Tanks.

The event is building on the success of its first edition, which took place in November 2022 in Lisbon/ Portugal with participants from 18 countries shaping the industry for a better tomorrow. Participants who chose the event in favor of other reputed events were decision makers from Holcim, Heidelberg Materials, Titan Cement, Cementos Argos, Cimsa, Secil or Dalmia Cement representing India, Brazil, South Africa, USA, Colombia as well as diverse countries in Europe.

During the first edition of CarbonZero Global Conference and Exhibition, the delegates agreed that the cement and construction industry need major changes in line with the reality that vary from updating industry standards, aligning with global effort, communicating interregionally and a clear commitment to changes including moving industry institutions. Clear policies and instruments are required for a clean and safe planet as circular economy is the optimum scenario the industry should tend towards.

Conclusions from various summits, conferences and meetings show that despite unprecedented climate distress, from radical weather changes with regional impact to local phenomena, we are still heading a one-way road towards climate disaster. Pledges are not being kept and solutions remain declarative. We need solutions now. www.industrylink.eu

CLEANER, SAFER, **MORE PRODUCTIVE** CONVEYING **SILO BLOCKAGE?** When a problem comes along like product accumulation inside your silos or storage vessels caused by humidity or inherently adhesive material, it often becomes necessary to knock buildup off interior walls. MARTIN HEAVY DUTY SILO WHIP Martin[®] Silo Cleaning provides a 24/7/365 turnkey service to break down those obstructions without damage to walls, bottoms or linings – and in many cases, without shutting down your operation.



Factory-direct service, training and sales: call Martin headquarters at 1-309-852-2384. Professional development options: click the Learning Center tab at martin-eng.com.