


Martin® ApronSeal™ Skirting



Martin® ApronSeal™ Skirting is a dual sealing system that prevents spillage without requiring service to maintain an effective seal. Martin® ApronSeal™ Skirting Systems provide dual-sealing surfaces. The primary and secondary seal is clamped to the chute wall with the self-adjusting secondary laying outward to create an effective dust seal that is out of the material flow.

Consult *Rubber Sealing System Selection Guide* (Form No. L3636) and *Urethane Sealing System Guide* (Form No. L4220) to select the proper Martin® ApronSeal™ product for your application.

Martin® ApronSeal™ Skirting



P/N CS7506005RX* (order quantity needed)
 * "X" indicates urethane color, "O" for orange and "G" for high temperature green.

- The multiple leg secondary can be trimmed off to fit free belt edge.
- Offers a dual sealing system in a two-piece, secondary seal that slides into the primary seal.
- 90 durometer urethane offers good chemical resistance and low-abrasion index characteristics.
- 60 in. (1524 mm) long strips with T-Slot connections on each end.
- Applicable on 0°, 20°, 35°, and 45° Troughing Angles.

ACCESSORIES ORDER INFORMATION

Product	Part #
Standard Angle Clamp Weldment with hardware including 1/2-13 studs, nuts & washers	32049 32049-H
Primary Seal Option, 5' (1524 mm) length	CS7506005RX*
Secondary Seal Option, 12' (3658 mm) length	100442-12
Martin® ApronSeal™ Clamp Quick Release fits standard & low-profile angle clamps	36273

* "X" indicates urethane color, "O" for orange and "G" for high temperature green.



TECHNICAL DATA SHEET


Angle clamps are used to clamp the Martin® ApronSeal™ Skirting to chute wall, approximately 9 in. (229 mm) of head space is required for proper mounting. Angle clamps are 6 ft (1829 mm) long with mount studs on 12-inch (305 mm) centers. Mounting height for studs will vary with troughing angle and type of Martin® ApronSeal™ used.

Consult Martin Engineering for mounting details.




MINIMUM FREE BELT EDGE—in. (mm)

Trough Angle	Martin® Apronseal™ Urethane Skirting
0°	3.75 (95)
20°	4.29 (109)
35°	4.50 (114)
45°	4.77 (121)

36" BW
35° TROUGH
SHOWN



Dimensions - in. (mm)



Martin Engineering USA
One Martin Place
Neponset, IL 61345-9766 USA
800 544 2947 or 309 852 2384
Fax 800 814 1553
www.martin-eng.com

**COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
ISO 9001**

Problem Solved™ GUARANTEED!

Form No. L4218-04/26
© Martin Engineering Company 2025, 2026