

EVO® Slider Cradle



The **EVO® Slider Cradle** utilizes low friction UHMW bars to support the belt at the outside of the load-carrying area. This stabilizes the belt line, eliminating the sag and bounce that spill material, and reducing the risk of catching lumps that can abrade the belt surface.

The low friction bars utilize a proprietary “box” design that allows the bars to be turned over to provide a second wear life from each bar. In the center of the cradle, idlers reduce the friction of carrying the loaded belt.

CRADLE SIZES AND FEATURES

			Dimensions—in. (mm)
Belt Width	Bars per Side	Stringer Width	Mounting Centers
36 (800-1000)	1	48 (1219)	45 (1143)
42 (1000-1200)	2	54 (1317)	51 (1295)
48 (1200-1400)	2	60 (1529)	57 (1448)
54 (1400-1600)	2	66 (1667)	63 (1600)
60 (1600-1800)	2	72 (1829)	69 (1753)

SPECIFICATIONS

UHMW Slider Cradle Bar	
Coefficient of Friction	0.5
Specific Gravity	0.94
Durometer	62 (Shore D)
Service Temp.	-20° to 160°F (-29° to 70°C)
Bar Part Number	UC-002040

Stainless Steel Slider Cradle Bars	
Bar Part Number for 304 SS	37502-C
Bar Part Number for 316 SS	37502-S

NOMENCLATURE — UCGS XX X XX X X X X X

- | | |
|--|--|
| <ol style="list-style-type: none"> 1. Part Number Prefix 2. The first XX indicates belt width. 3. The next X indicates stringer spacing:
S = Standard Base
W = Wide Base 4. The next XX indicates trough angle:
20 = 20 degrees
35 = 35 degrees
45 = 45 degrees 5. The next X indicates roll option:
6 = 6" diameter roll
F = Frame only (no rolls)
N = No roll or center sleeve weldment | <ol style="list-style-type: none"> 6. The next X indicates bar type:
P = UHMW
U = Urethane
S = Stainless Steel 7. The next X indicates paint options:
P = Painted
S = Stainless Steel 8. The next X indicates shipping options:
A = Fully assembled
C = Component parts loose 9. The next X indicates stringer type:
E = EVO®
S = Standard |
|--|--|



Martin Engineering USA
 One Martin Place
 Neponset, IL 61345-9766 USA
 800 544 2947 or 309 852 2384
 Fax 800 814 1553
 www.martin-eng.com

**COMPANY WITH
 QUALITY SYSTEM
 CERTIFIED BY DNV
 = ISO 9001:2008 =**